


### ● Features:

1. Chip material: AlInGaP(Green)
2. Emitted color : Green
3. Lens Appearance :Green Diffused
4. Designed for ease in circuit board assembly.
5. Black case enhance contrast ratio.
6. Solid state light source.
7. Reliable and rugged.
8. 3mm diameter package.
9. This product don't contained restriction substance, compliance ROHS standard.

### ● Applications:

1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

### ● Package dimensions



### ● Absolute Maximum Ratings( $T_a=25^\circ\text{C}$ )

Parameter	Symbol	Green	Unit
Power Dissipation	$P_d$	75	mW
Forward Current	$I_F$	30	mA
Peak Forward Current* <sup>1</sup>	$I_{FP}$	150	mA
Reverse Voltage	$V_R$	5	V
Operating Temperature	$T_{opr}$	$-30^\circ\text{C} \sim 80^\circ\text{C}$	
Storage Temperature	$T_{stg}$	$-40^\circ\text{C} \sim 85^\circ\text{C}$	
Soldering Temperature	$T_{sol}$	$260^\circ\text{C}$ (for 5 seconds)	




\*<sup>1</sup>Condition for  $I_{FP}$  is pulse of 1/10 duty and 0.1msec width.

● Electrical and optical characteristics(Ta=25°C)



Parameter	Symbol	Condition	Color	Min.	Typ.	Max.	Unit
Forward Voltage	$V_F$	$I_F=20\text{mA}$	Green	1.8		2.4	V
Luminous Intensity	$I_v$	$I_F=20\text{mA}$	Green	30		60	mcd
Reverse Current	$I_R$	$V_R=5\text{V}$	Green	-	-	5	$\mu\text{A}$
Peak Wave Length	$\lambda_p$	$I_F=20\text{mA}$	Green	-	-	-	nm
Dominant Wave Length	$\lambda_d$	$I_F=20\text{mA}$	Green	565	568	571	nm
Spectral Line Half-width	$\Delta\lambda$	$I_F=20\text{mA}$	Green	-	-	-	nm
Viewing Angle	$2\theta_{1/2}$	$I_F=20\text{mA}$	Green	-	45	-	deg

● Typical Electro-Optical Characteristics Curves


Green



Forward Current Vs Relative luminous Intensity



## ●Dip Soldering



1. Please avoid any external stress applied to the lead-frames and epoxy while the LEDs are at high temperature, especially during soldering
2. DIP soldering and hand soldering should not be done more than one time.
3. After soldering, avoid the epoxy lens from mechanical shock or vibration until the LEDs are back to room temperature.
4. Avoid rapid cooling during temperature ramp-down process
5. Although the soldering condition is recommended above,  
soldering at the lowest possible temperature is feasible for the LEDs

## ●IRON Soldering

A: Max: 350°C Within 3 sec. One time only.

B: The products of 3mm without flange, welding condition of flat plate PCB Max: 350°C  
Within 2 sec. One time only

