


● Features:

1. Chip material: AlInGaP (Yellow)
2. Emitted color : Yellow
3. Lens Appearance : Yellow Diffused
4. Designed for ease in circuit board assembly.
5. Black case enhance contrast ratio.
6. Solid state light source.
7. Reliable and rugged.
8. 3mm diameter package.
9. This product don't contained restriction substance, compliance ROHS standard.

● Applications:

1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

● Package dimensions



● Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Yellow	Unit
Power Dissipation	Pd	80	mW
Forward Current	I _F	30	mA
Peak Forward Current* ¹	I _{FP}	100	mA
Reverse Voltage	V _R	1	V
Operating Temperature	Topr	-40°C~80°C	
Storage Temperature	Tstg	-40°C~85°C	
Soldering Temperature	Tsol	260°C (for 5 seconds)	




*¹Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

● **Electrical and optical characteristics(Ta=25°C)**


Parameter	Symbol	Condition	Color	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F=20\text{mA}$	Yellow	1.8		2.4	V
Luminous Intensity	I_v	$I_F=20\text{mA}$	Yellow	20		80	mcd
Reverse Current	I_R	$V_R=5\text{V}$	Yellow	-	-	10	μA
Peak Wave Length	λ_p	$I_F=20\text{mA}$	Yellow	-	-	-	nm
Dominant Wave Length	λ_d	$I_F=20\text{mA}$	Yellow	585	590	595	nm
Spectral Line Half-width	$\Delta\lambda$	$I_F=20\text{mA}$	Yellow	-	30	-	nm
Viewing Angle	$2\theta_{1/2}$	Yellow	Yellow	-	40	-	deg

● **Typical Electro-Optical Characteristics Curves**


Yellow



Forward Current Vs Relative luminous Intensity



●Dip Soldering



1. Please avoid any external stress applied to the lead-frames and epoxy while the LEDs are at high temperature, especially during soldering
2. DIP soldering and hand soldering should not be done more than one time.
3. After soldering, avoid the epoxy lens from mechanical shock or vibration until the LEDs are back to room temperature.
4. Avoid rapid cooling during temperature ramp-down process
5. Although the soldering condition is recommended above, soldering at the lowest possible temperature is feasible for the LEDs

●IRON Soldering

A : Max : 350°C Within 3 sec. One time only.

B : The products of 3mm without flange, welding condition of flat plate PCB Max : 350°C Within 2 sec. One time only

