

SPECIFICATION FOR APPROVAL

Date : 2022/6/14

<i>Conductive Polymer Aluminum Solid Capacitor</i>		<i>GPL Series</i>								
Capacitance : 6.8 μF	Tolerance : $\pm 20\%$	Type : 直立式								
Voltage : 160 V DC	Part No. : GPL-6.8M160V0812									
Dimension (mm)										
		<table border="1"> <tr> <td>φD</td><td>8 ± 1.5</td></tr> <tr> <td>P</td><td>5.0 ± 0.5</td></tr> <tr> <td>L</td><td>12 ± 1.5</td></tr> <tr> <td>d</td><td>0.6 ± 0.1</td></tr> </table>	φD	8 ± 1.5	P	5.0 ± 0.5	L	12 ± 1.5	d	0.6 ± 0.1
φD	8 ± 1.5									
P	5.0 ± 0.5									
L	12 ± 1.5									
d	0.6 ± 0.1									
Specification :										
1 Operating Temperature Range	: -55 °C ~ +125 °C									
2 Leakage Current (μA)	: $I \leq 217 \mu\text{A}$ (After 2 minutes application of rated.)									
3 Surge Voltage DC	: Rated voltage $\times 1.15\text{ V}$									
4 Dissipation Factor (Tan δ)	: 0.12 MAX. (20°C/120Hz)									
5 Equivalent series resistance(ESR)	: 130 mΩ MAX. (20°C/100KHz to 300KHz)									
6 Max. Permissible ripple current	: 280 mA/125°C/100KHz (720mA/105°C/100KHz)									
7 High temperature & Low temperature characteristic	<table border="1"> <tr> <td>$Z(-55^\circ\text{C})/Z(+20^\circ\text{C})$</td><td>$\leq 1.25$</td></tr> <tr> <td>$Z(+125^\circ\text{C})/Z(+20^\circ\text{C})$</td><td>$\leq 1.25$</td></tr> </table>		$Z(-55^\circ\text{C})/Z(+20^\circ\text{C})$	≤ 1.25	$Z(+125^\circ\text{C})/Z(+20^\circ\text{C})$	≤ 1.25				
$Z(-55^\circ\text{C})/Z(+20^\circ\text{C})$	≤ 1.25									
$Z(+125^\circ\text{C})/Z(+20^\circ\text{C})$	≤ 1.25									
8 Load Life Test	: The following specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage is applied for 16V~25V 2000 hours, $\geq 35\text{V}$ 1500 hours at 125°C. The capacitor shall meet with following limits :									
	<table border="1"> <tr> <td>Capacitance Change</td><td>$\leq \pm 30\%$ of initial value</td></tr> <tr> <td>Dissipation Factor</td><td>$\leq 300\%$ of specified value</td></tr> <tr> <td>ESR</td><td>$\leq 300\%$ of specified value</td></tr> <tr> <td>Leakage Current</td><td>\leq initial specified value</td></tr> </table>		Capacitance Change	$\leq \pm 30\%$ of initial value	Dissipation Factor	$\leq 300\%$ of specified value	ESR	$\leq 300\%$ of specified value	Leakage Current	\leq initial specified value
Capacitance Change	$\leq \pm 30\%$ of initial value									
Dissipation Factor	$\leq 300\%$ of specified value									
ESR	$\leq 300\%$ of specified value									
Leakage Current	\leq initial specified value									
9 High temperature & High humidity : (Constant)	After storing for 1000 hours at 60°C、90~95% R.H.									
	<table border="1"> <tr> <td>Capacitance Change</td><td>$\leq \pm 20\%$ of initial value</td></tr> <tr> <td>Dissipation Factor</td><td>$\leq 150\%$ of specified value</td></tr> <tr> <td>ESR</td><td>$\leq 150\%$ of specified value</td></tr> <tr> <td>Leakage Current</td><td>\leq initial specified value</td></tr> </table>		Capacitance Change	$\leq \pm 20\%$ of initial value	Dissipation Factor	$\leq 150\%$ of specified value	ESR	$\leq 150\%$ of specified value	Leakage Current	\leq initial specified value
Capacitance Change	$\leq \pm 20\%$ of initial value									
Dissipation Factor	$\leq 150\%$ of specified value									
ESR	$\leq 150\%$ of specified value									
Leakage Current	\leq initial specified value									