



# SPECIFICATION FOR APPROVAL

Date : 2022/6/2

<i>Conductive Polymer Aluminum Solid Capacitor</i>		<b>UPL Series</b>									
Capacitance : 2500 $\mu$ F	Tolerance : $\pm 20 \%$	Type : 直立式									
Voltage : 16 V DC	Part No. : UPL-2500M16V1021										
Dimension (mm)											
		<table border="1"> <tr> <td><math>\phi</math> D</td> <td>10 <math>\pm 1.5</math></td> </tr> <tr> <td>P</td> <td>5.0 <math>\pm 0.5</math></td> </tr> <tr> <td>L</td> <td>21 <math>\pm 1.5</math></td> </tr> <tr> <td>d</td> <td>0.6 <math>\pm 0.1</math></td> </tr> </table>		$\phi$ D	10 $\pm 1.5$	P	5.0 $\pm 0.5$	L	21 $\pm 1.5$	d	0.6 $\pm 0.1$
$\phi$ D	10 $\pm 1.5$										
P	5.0 $\pm 0.5$										
L	21 $\pm 1.5$										
d	0.6 $\pm 0.1$										
<b>Specification :</b>											
1 Operating Temperature Range	:	- 55 $^{\circ}$ C ~ + 125 $^{\circ}$ C									
2 Leakage Current ( $\mu$ A)	:	$I \leq 8000 \mu$ A (After 2 minutes application of rated.)									
3 Surge Voltage DC	:	Rated voltage x 1.15 V									
4 Dissipation Factor (Tan $\delta$ )	:	0.12 MAX. (20 $^{\circ}$ C/120Hz)									
5 Equivalent series resistance(ESR)	:	13 m $\Omega$ MAX. (20 $^{\circ}$ C/100KHz to 300KHz)									
6 Max. Permissible ripple current	:	3600 mA/125 $^{\circ}$ C/100KHz (10000mA/105 $^{\circ}$ C/100KHz)									
7 High temperature & Low temperature characteristic	:	<table border="1"> <tr> <td>Z(-55<math>^{\circ}</math>C)/Z(+20<math>^{\circ}</math>C)</td> <td><math>\leq 1.25</math></td> </tr> <tr> <td>Z(+125<math>^{\circ}</math>C)/Z(+20<math>^{\circ}</math>C)</td> <td><math>\leq 1.25</math></td> </tr> </table>		Z(-55 $^{\circ}$ C)/Z(+20 $^{\circ}$ C)	$\leq 1.25$	Z(+125 $^{\circ}$ C)/Z(+20 $^{\circ}$ C)	$\leq 1.25$				
Z(-55 $^{\circ}$ C)/Z(+20 $^{\circ}$ C)	$\leq 1.25$										
Z(+125 $^{\circ}$ C)/Z(+20 $^{\circ}$ C)	$\leq 1.25$										
8 Load Life Test	:	The following specifications shall be satisfied when the capacitors are restored to 20 $^{\circ}$ C after the rated voltage is applied for 16V~25V 2000 hours, $\geq 35$ V 1500 hours at 125 $^{\circ}$ C. The capacitor shall meet with following limits : <table border="1"> <tr> <td>Capacitance Change</td> <td><math>\leq \pm 30\%</math> of initial value</td> </tr> <tr> <td>Dissipation Factor</td> <td><math>\leq 300\%</math> of specified value</td> </tr> <tr> <td>ESR</td> <td><math>\leq 300\%</math> of specified value</td> </tr> <tr> <td>Leakage Current</td> <td><math>\leq</math> initial specified value</td> </tr> </table>		Capacitance Change	$\leq \pm 30\%$ of initial value	Dissipation Factor	$\leq 300\%$ of specified value	ESR	$\leq 300\%$ of specified value	Leakage Current	$\leq$ initial specified value
Capacitance Change	$\leq \pm 30\%$ of initial value										
Dissipation Factor	$\leq 300\%$ of specified value										
ESR	$\leq 300\%$ of specified value										
Leakage Current	$\leq$ initial specified value										
9 High temperature & High humidity : (Constant)	:	After storing for 1000 hours at 60 $^{\circ}$ C 、90~95% R.H. <table border="1"> <tr> <td>Capacitance Change</td> <td><math>\leq \pm 20\%</math> of initial value</td> </tr> <tr> <td>Dissipation Factor</td> <td><math>\leq 150\%</math> of specified value</td> </tr> <tr> <td>ESR</td> <td><math>\leq 150\%</math> of specified value</td> </tr> <tr> <td>Leakage Current</td> <td><math>\leq</math> initial specified value</td> </tr> </table>		Capacitance Change	$\leq \pm 20\%$ of initial value	Dissipation Factor	$\leq 150\%$ of specified value	ESR	$\leq 150\%$ of specified value	Leakage Current	$\leq$ initial specified value
Capacitance Change	$\leq \pm 20\%$ of initial value										
Dissipation Factor	$\leq 150\%$ of specified value										
ESR	$\leq 150\%$ of specified value										
Leakage Current	$\leq$ initial specified value										