



承 認 書

| | | | | | | | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------|-----------------------------------------------------------------------------------|------------|---|---|---|---|---|----|
| 鋁質電解電容器 105°C XF Series | | | 日期：111年06月08日 | | | | | | | |
| 容 量： 2200 μ F | | 誤差度： $\pm 20\%$ | | 形 狀： 直 立 式 | | | | | | |
| 電 壓： 16 V DC | | 數 量： PCS | | 結 論： | | | | | | |
| Shape & Dimension (mm) | | | 1. 承 認 2. 有條件地承認 3. 退 件 | | | | | | | |
| | | | D : 13 ± 0.5 F : 5.0 ± 0.5 L : 25.0 ± 1.5 d : 0.6 ± 0.05 | | | | | | | |
| Specification | | | | | | | | | | |
| F = 120 HZ | | | T = 20 °C | | | | | | | |
| 1 Operating Temperature Range | | : - 40 °C + 105 °C | | | | | | | | |
| 2 Leakage Current | | : I \leq 0.01 CV or 3uA | | | | | | | | |
| 3 Surge Voltage DC | | : 20 VOLT | | | | | | | | |
| 4 Dissipation Factor (Tan δ) | | : 0.16 MAX. | | | | | | | | |
| 5 Max.Impedance (20°C/100KHz) | | : 26 m Ω MAX. | | | | | | | | |
| 6 Max. Permissible ripple current | | : 2240 mA/105°C/100KHz | | | | | | | | |
| 7 Load Test : After 10000 hours application of W.V. at 105°C The capacitor shall meet with following limits : Capacitance Change : $\leq \pm 25\%$ of initial value Dissipation Factor : $\leq 200\%$ of initial specified value Leakage Current : \leq initial specified value | | | | | | | | | | |
| INITIAL TEST | | | | | | | | | | |
| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 |
| 容 量 μ F | | | | | | | | | | |
| 洩漏電流 | | | | | | | | | | |
| DF 值 | | | | | | | | | | |
| R 值 | | | | | | | | | | |