



1SC5050VGB00CB05

- ◆Outline (L* W*H): 5.0*5.0*1.6mm
- ◆Good thermal dissipation & optical uniformity



Table of Contents

Product Code Method-----	2
Maximum Rating-----	2
Typical Product Characteristics-----	3
Range of Bins-----	3
Color Coordinate Comparison-----	5
Electronic-Optical Characteristics-----	6
Dimensions -----	7
Reflow Profile-----	8
Test Circuit and Handling Precautions-----	9
Packing-----	10
Precautions -----	12
Test Items and Results of Reliability-----	13

Features

- Forward current: $R \leq 50\text{mA}$; $G\&B \leq 30\text{mA}$
- Typical view angle 50% Iv: 120°
- Lens color: water transparent
- RoHS and REACH-compliant
- Qualified according to JEDEC moisturevity Level 5
- ESD level 1kV(HBM)

Applications

- Indoor decorating
- Outdoor lighting for amusement
- Consumer electronics
- Other applications

■ Product Code Method

1 - S - C - 5050 - VGB0 - 0 - C - B - 05

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

①	②	③	④	⑤
Process Type	Category	LED Type	Lead Frame Size	Dice wavelength & luminous rank
1: normal process	S: SMD LED	C: PLCC top view D: PLCC side view	5050: 5.0*5.0mm	V:red G:green B:blue

⑥	⑦	⑧	⑨
Lap Polarity	Cap Color	PCB Module Code	Flow Code
0: non-common anode and non-common cathode	C: water transparent	B: article mode	05: no expression above meaning for company

■ Maximum Rating(Ta=25°C)

Characteristics	Symbol	Rating	Unit
DC Forward Current	I _F	G&B≤30 / R≤50	mA
Pulse Forward Current ^{*3}	I _{PF}	100	mA
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	G&B:80 / R:100	mW
Junction Temperature	T _J	110	°C
Operating Temperature Range	T _{OP}	-40~85	°C
Storage Temperature Range	T _{STG}	-40~100	°C
Soldering Temperature ^{*4}	T _{SD}	260	°C

Notes 1: There is no maximum or typical voltage parameter

2: For other ambient, limited setting of current will be depended on de-rating curves.

3: Duty 1/10, pulse width 0.1ms

4: The maximum of soldering time is 5 seconds in T_{SD}

■ **Typical Product Characteristics(Ta=25℃)**

Characteristics	Symbol		Min.	Typ.	Max.	Unit	Test condition
Forward Voltage	V _F	R	1.8	2.0	2.6	V	I _F =20mA
		G	2.8	3.2	3.6		I _F =20mA
		B	2.8	3.2	3.6		I _F =20mA
Reverse Current	I _R		-	-	10	μA	V _R = 5V
Luminous Intensity	I _v	R	575	700	-	mcd	I _F =20mA
		G	1280	1750	-		I _F =20mA
		B	245	320	-		I _F =20mA
Dominant Wavelength	λ _d	R	615	-	630	nm	I _F =20mA
		G	520	-	535		I _F =20mA
		B	461	-	476		I _F =20mA
View Angle	2θ _{1/2}		-	120	-	deg	I _F =20mA

Notes: 1. Measurement Errors:

Forward Voltage: ±0.1V, Luminous Intensity: ±10%I_v, Dominant Wavelength: ±1.0nm

2. Electrical-Optical Characteristics (Ta=25℃)

■ **Range of Bins (I_F=20mA)**

1).Forward Voltage Bins (I_F=20mA)

Bin code		Min. V _F (V)	Max. V _F (V)
R	C	1.8	2.0
	D	2.0	2.2
	E	2.2	2.4
	F	2.4	2.6
G&B	J	2.8	3.0
	K	3.0	3.2
	L	3.2	3.4
	M	3.4	3.6



■ Range of Bins


2).Luminous Intensity Bins

Bin code		Min. Iv (mcd)	Max. Iv (mcd)
R	13	575	720
	14	720	900
	15	900	1125
G	12	1280	1600
	13	1600	2000
	14	2000	2500
B	11	245	305
	12	305	385
	13	385	480

3).Dominant Wavelength Bins ($I_F=20\text{mA}$)

Bin Code		Min. λ_d (nm)	Max. λ_d (nm)
R	2	615	620
	3	620	625
	4	625	630
G	2	520	525
	3	525	530
	4	530	535
B	2	461	466
	3	466	471
	4	471	476

■ Color Coordinate Comparison




Color Rank


Bin code	x	y	x	y	x	y	x	y
A	0.307	0.3072	0.3287	0.2948	0.3091	0.2712	0.2865	0.2819
B	0.3287	0.2948	0.3504	0.2824	0.3318	0.2605	0.3091	0.2712
C	0.2865	0.2819	0.3091	0.2712	0.2899	0.2482	0.2667	0.2578
D	0.3091	0.2712	0.3318	0.2605	0.3132	0.2387	0.2899	0.2482
E	0.2667	0.2578	0.2899	0.2482	0.27	0.2227	0.247	0.232
F	0.2899	0.2482	0.3132	0.2387	0.293	0.2134	0.27	0.2227
G	0.3318	0.2605	0.3524	0.2513	0.3358	0.2299	0.3132	0.2387
H	0.293	0.2134	0.3132	0.2387	0.3358	0.2299	0.315	0.204
I	0.3319	0.2607	0.3504	0.2824	0.3695	0.2719	0.3524	0.2513
J	0.2609	0.3332	0.2797	0.355	0.3036	0.342	0.2849	0.3191
K	0.2851	0.3196	0.3036	0.342	0.3243	0.328	0.3066	0.3064
L	0.2406	0.3064	0.2609	0.3332	0.2849	0.3196	0.2648	0.2944
M	0.264	0.294	0.2849	0.3196	0.3068	0.3072	0.2863	0.282
N	0.22	0.2783	0.2408	0.3068	0.2643	0.294	0.2444	0.2672
O	0.2444	0.2672	0.2646	0.294	0.2863	0.282	0.2671	0.2585
P	0.22	0.2783	0.1996	0.2513	0.225	0.241	0.2444	0.2672
Q	0.2444	0.2672	0.2244	0.2407	0.2471	0.232	0.2669	0.2579
R	0.1996	0.2513	0.1792	0.2243	0.2056	0.2148	0.225	0.241
S	0.225	0.241	0.2056	0.2148	0.2273	0.2061	0.2471	0.232
T	0.1792	0.2243	0.1588	0.1973	0.1862	0.1886	0.2056	0.2148
U	0.2056	0.2148	0.1862	0.1886	0.2075	0.1802	0.2273	0.2061

Electronic-Optical Characteristics


1). Relative Spectral Distribution




2). Typical Spatial Distribution




3). Relative Luminous Flux .Current




4). Relative Luminous Flux .Ambient Temperature




5). Electrical Characteristics




6). Forward Voltage Temperature




7). Wavelength and current




8). Thermal Design



■ Dimensions




Recommend Padlayout RECOMMEND PADLAYOUT



- § All dimensions are in millimeters.
- § Tolerance is ± 0.1 mm unless other specified
- § Specifications are subject to change without notice

■ Reflow Profile

1. IR reflow soldering Profile for Lead Free solder




Notes:

1. We recommend the reflow temperature 240°C ($\pm 5^\circ\text{C}$). the maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the silicone resin while it is exposed to high temperature.
3. Number of reflow process shall be less than 3 times.

■ Test Circuit and Handling Precautions

1. Test circuit



2. Handling precautions

2.1. Over-current-proof

Customer must apply resistors for protection; otherwise slight voltage shift will cause big current change (Burn out will happen).

2.2. Storage

1). It is recommended to store the products in the following conditions:

Humidity: 60% R.H. Max.

Temperature : 5°C~30°C (41°F~86°F)

2). Shelf life in sealed bag: 12 month at <5°C~30°C and <60% R.H. after the package is Opened, the products should be used within 48 hours or they should be keeping to stored at $\leq 20\%$ R.H. with zip-lock sealed.

2.3. Baking

Suggest packing open after 48 hours, before use baking products, conditions as follows:


1). 60±3°C X 6hrs and <5%RH, for reel

2). 125±3°C X 2hrs, for single LED

It shall be normal to see slight color fading of carrier (light yellow) after baking in process


■ Packing

● Dimensions of Reel (Unit: mm)




Note: 01.The tolerance unless mentioned is ± 0.2 mm.
02.The measured unit is "mm".

● Dimensions of Tape (Unit: mm)



● Arrangement of Tape




Notes:

1. Empty component pockets are sealed with top cover tape
2. The max loss number of SMD is 2pcs
3. The cathode is oriented towards the tape sprocket hole in accordance with ANSI/EIA RS-481 specifications
4. 1000pcs per reel

■ Packing

● Packaging specifications



Notes:

Reeled product (max.1000) is packed in a sealed moisture-proof bag. Five bags are packed in an inner box (size: about 260 X 230 X 100 mm) and four inner boxes are in an outer box (size: about 480 X 275 X 215mm). On the label of moisture-proof bag, there should be the information of Part No., Lot No. and quantity number; also the total quantity number should be on inspection request form on outer box.

■ Precautions


1. Abnormal situation caused by improper setting of collet

To choose the right collet is the key issue in improving the product's quality. LED is different from other electronic components, which is not only about electrical output but also for optical output. This characteristic made LED more fragile in the process of SMT. If the collet's lowering down height is not well set, it will bring damage to the gold wire at the time of collet's picking up and loading which will cause the LED fail to light up, light up now and then or other quality problems


2. How to choose the collet

During SMT, please choose the collet that has larger outer diameter than the lighting area of lens, in case that improper position of collet will damage the gold wire inside the LED. Different collets fit for different products, please refer to the following pictures cross out

Outer diameter of collet should be larger than the lighting area



Picture 1(√)



Picture 2(X)

3. Other points for attention

- A. No pressure should be exerted to the epoxy shell of the SMD under high temperature.
- B. Do not scratch or wipe the lens since the lens and gold wire inside are rather fragile and cross out easy to break.
- C. LED should be used as soon as possible when being taken out of the original package, and should be stored in anti-moisture and anti-ESD package.

4. This usage and handling instruction is only for your reference.

■ Test Items and Results of Reliability

Test Item	Test Conditions	Duration/ Cycle	Ac/Re	Number of Damage	Reference
Normal Temperature Life	Ta=23°C(±5°C) I _F =20mA	1008 hrs	0/1	0/22	JESD22 A-108
High Temperature Life	Ta=85°C(±5°C) I _F =20mA	1008 hrs	0/1	0/22	JESD22 A-108
High Humidity Heat Life	Ta=85°C(±5°C) RH=85% I _F =20mA	1008 hrs	0/1	0/22	JESD22 A-108
Thermal shock	-45°C/30min~105°C /30min (±5°C)	1008 hrs	0/1	0/22	JESD22 A-104
Electrostatic Discharge (ESD) Test	According to the SPEC	3 cycles	0/1	0/22	AEC Q101-001
Low Temperature Storage	T _a =-40°C	1008 hrs	0/1	0/22	JESD22-A103D
High Temperature Storage	T _a =125°C	1008 hrs	0/1	0/22	JESD22-A103D

*Criteria for Judging

Item	Symbol	Condition	Criteria for Judgment of Pass	
			Min	Max
Forward Voltage	V _F	I _F =20mA	-	USL* ¹ ×1.1
Reverse Current	I _R	V _R = 5V	-	10μA
Luminous Intensity	I _v	I _F =20mA	LSL* ² ×0.7	-

[Note] USL*¹: Upper Specification Level

LSL*²: Lower Specification Level